



SOLARIS
QUALITY ATTACHMENTS



TE SERIE 3

(888) 754-3609 | sales@solarisattachments.com
www.solarisattachments.com

SPECIFICATIONS

Model	Weight Class	Width	Dimensions	Weight	Motor Displacement	Oil (gpm)	PSI	Transmission	Rotor	Hammers
TE1.3-70 K/M	1.5-4.0	27.6"	37"x22"x18"	286 lbs	8-11-16	5.3-8-11	2466-3191	Direct	Helical	10
TE2.3-90 K/M	1.5-4.0	35.5"	45"x22"x18"	331 lbs	11-16	8-11	2466-3191	Direct	Helical	14



- SHREDDER WITH 10 INTERCHANGEABLE HAMMERS & 20 “Y” KNIVES ON A HELICAL BALANCED ROTOR
- DIRECT DRIVE GEAR MOTOR GR2 8-11-16 CC / REV WITH ANTI-SHOCK ANTI-CAVITATION VALVE
- FLOW 5.3-8-11 gpm PRESSURE 2466-3191 psi.
- RUBBER PROTECTION
- CE COMPLIANT
- STANDARD ROLLER ADJUSTABLE IN THREE POSITIONS



SOLARIS
QUALITY ATTACHMENTS

(888) 754-3609 | sales@solarisattachments.com
www.solarisattachments.com