

# SOLARIS SWINGING PLANERS




## FEATURES

- Designed for Asphalt or Concrete
- Mechanical Depth Adjustment with Skid Frame & Threaded Bar
- Swinging Frame Linkage to Dipper Stick
- Highly Reliable & Durable Construction



# SOLARIS SWINGING PLANERS



MODEL		CPB 30.13	CPB 40.13	CPB 45.15	CPB 60.17
		NO CASE DRAIN - 2 LINES		CASE DRAIN REQUIRED	
Specifications	units				
Working Width - Standard Drum	in.	12	16	18	24
Working Depth - Standard Drum	in.	0 - 5	0 - 5	0 - 6	0 - 7
Standard Asphalt Teeth	#	48	48	54	66
Flow Range	gpm	12 - 21	21-Dec	24 - 37	32 - 42
Pressure Range	psi	2400 - 4400		2400 - 4400	
Weight	lbs.	881	926	1,389	1,653
Minimum Distance From Wall	in.	3.1			
Depth Adjustment		manual			
Swinging Support Rotation		135 degrees			
Average Milling Speed (Standard Drum at 50% Depth)	ft./min.	2 - 10		2 - 15	
For Excavators	lbs.	6,600 - 13,200	12,100 - 20,900	15,400 - 28,700	26,500 - 39,700
For Backhoes	lbs.	N/A	13,200 - 19,800	16,500 - 26,500	N/A
 <b>Dimensions</b>	A - in.	26	26	27	33
	B - in.	33	33	34	35
	C - in.	35	35	36	38



[www.solarisattachments.com](http://www.solarisattachments.com)

Call (888) 754-3609

Email: [sales@solarisattachments.com](mailto:sales@solarisattachments.com)