

WG Wood Grabber



AREAS OF APPLICATION



UNBEATABLE STRENGTH

The WG series is **exceptionally rugged**, with load capacity and **clamping force** which makes it optimal for gripping logs and felled timber.

SAFETY GUARANTEED

The **check valve** standard on all models guarantees safety; installed on the clamping cylinder, it prevents the claws from opening if the pressure fails.

HIGHLY FLEXIBLE

The grab can be equipped with **360° hydraulic rotation**, which greatly facilitates the operator when collecting cut material, for a faster, more effective job.



Tons (lb)	1,2 - 1,8 (2646-3968)	1,8 - 3,5 (3968-7716)	3,5 - 4,0 (7716-8818)	4,0 - 5,0 (8818-11023)	5,0 - 7,0 (11023-15432)	7,0 - 8,0 (15432-17637)	8,0 - 10,0 (17637-22046)	10,0 - 12,0 (22046 - 26455)	12,0-15,0 (26455-33069)	15,0-18,0 (33069-39683)		
MOD.	WG 1000	WG 1100	WG 1300	WG 1300HD	WG 1500	WG 1750	WG 1650	WG 1800	WG 2000	WG 1800HD	WG 2000HD	
Without coupling	kg (lb)	48 (106)	85 (187)	118 (260)	131 (289)	196 (432)	265 (584)	280 (617)	400 (882)	450 (992)	440 (970)	505 (1113)
Max.	kg (lb)	500 (1102)	1900 (4188)	2100 (4630)	2100 (4630)	3100 (6834)	3500 (7716)	4000 (8818)	6000 (13228)	6000 (13228)	7000 (15432)	7000 (15432)

The WG SP grab is designed **without guards** at the ends of the claws, making it particularly suitable for **handling branches**. The claws are shaped for **neat collection of the product**, with excellent compacting.



Tons (lb)	1,2 - 1,8 (2646-3968)	1,8 - 3,5 (3968-7716)	3,5 - 4,0 (7716-8818)	4,0 - 5,0 (8818-11023)	5,0 - 7,0 (11023-15432)	7,0 - 8,0 (15432-17637)	8,0 - 10,0 (17637-22046)	10,0 - 12,0 (22046 - 26455)	12,0 - 16,0 (26455 - 35274)	
MOD.	WG 1100SP	WG 1100SP	WG 1300SP	WG 1300SP	WG 1500SP	WG 1650SP	WG 1800SP	WG 1800SP	WG 2000SP	
Without coupling	kg (lb)	100 (220)	100 (220)	140 (309)	140 (309)	225 (496)	300 (661)	440 (970)	440 (970)	495 (1091)
Max.	kg (lb)	1900 (4188)	1900 (4188)	2100 (4630)	2100 (4630)	3100 (6834)	4000 (8818)	6000 (13228)	6000 (13228)	6000 (13228)

