

Hydraulic Log Splitter
For Hi-Flow Skid Steers, 17-40 gpm





**For Hi-Flow
Skid Steers**

**55 AUGERS
6 in. - 48 in. Dia**

- Torque Range: 2,004 - 6,012 ft-lb
- Oil Pressure Range: 1,160 - 3,481 psi
- Oil Flow Range: 19 - 40 gpm
- Speed Range: 33 - 70 rpm
- Unit Height: 31 in.
- Unit Diameter: 11 in.
- Unit Weight: 260 lbs
- Hitch Options: Single Pin Hitch
Double Pin Hitch
Cradle Hitch
- Optional Extras: 2 Way Valve
- Output Shaft Std: 2.5 in. Hex
- Output Shaft Opt: 2.96 in. Square



Double Pin Hitch



Cradle Hitch



Single Pin Hitch



Skid Steer Mount



Log Splitter Pilot



Drive Unit

GUIDE TO DRILLING PERFORMANCE*

AUGER DIA	DRILLING DEPTH IN FEET**		
	SOFT	MEDIUM	HARD
6 in	20 ft	18 ft	16 ft
8 in			
9 in			
10 in			
12 in			
14 in			
15 in	↓	↓	↓
16 in	20 ft	18 ft	16 ft
18 in	16 ft	15 ft	13 ft
20 in	16 ft	15 ft	13 ft
22 in	16 ft	15 ft	13 ft
24 in	16 ft	15 ft	13 ft
28 in	15 ft	13 ft	12 ft
30 in	13 ft	12 ft	10 ft
32 in	13 ft	12 ft	10 ft
36 in	11 ft	10 ft	10 ft
40 in	11 ft	10 ft	10 ft
48 in	10 ft	9 ft	8 ft



2.96 in. Square
2.5 in. Hex



2 Way Valve
Converts single acting hammer circuit into 2 Way auxiliary flow

Log Splitter for Hi-Flow Skid Steers, 17- 40 gpm
S5 6000-40 Drive Unit, includes hoses and flat-faced couplings
Log Splitter Cone Kit
Skid Steer Frame

Solaris Attachments

(888) 754-3609

sales@solarisattachments.com

www.solarisattachments.com



SOLARIS
QUALITY ATTACHMENTS