

Hydraulic Log Splitter
For Standard Flow Skid Steers, 13 - 30 gpm





**For Standard Flow
Skid Steers**
S4 AUGERS
4 in. - 36 in. Dia

Torque Range: 1,106 - 3,318 ft-lb
 Oil Pressure Range: 1,160 - 3,481 psi
 Oil Flow Range: 13 - 30 gpm
 Speed Range: 42 - 97 rpm
 Unit Height: 26 in.
 Unit Diameter: 10 in.
 Unit Weight: 166 lbs
 Hitch Options: Single Pin Hitch
 Double Pin Hitch
 Cradle Hitch
 Output Shaft Std: 2 in. Hex
 Output Shaft Opt: 2.56 in. Round
 2.25 in. Square



Skid Steer Mount



Log Splitter Pilot



Earth Drill Drive Unit

GUIDE TO DRILLING PERFORMANCE*

AUGER DIA	DRILLING DEPTH IN FEET**		
	SOFT	MEDIUM	HARD
4 in	13 ft	12 ft	10 ft
6 in			
8 in			
9 in			
10 in			
12 in			
14 in			
15 in			
16 in			
18 in			
20 in			
22 in	↓	↓	↓
24 in	13 ft	12 ft	10 ft
28 in	10 ft	9 ft	8 ft
30 in	8 ft	8 ft	7 ft
32 in	7 ft	6 ft	5 ft
36 in	5 ft	5 ft	4 ft

Log Splitter for Standard Flow Skid Steers, 13 - 30 gpm
S4 3300-30 Drive Unit, includes hoses & flat-faced couplings
Log Splitter Cone Kit
Skid Steer Frame

Solaris Attachments
(888) 754-3609
sales@solarisattachments.com
www.solarisattachments.com