

EARTH DRILL ML RANGE



DEDICATED MINI LOADER EARTH DRILLS

The Earth Drill range ML1100-13 to ML2100-17 is the perfect choice for Mini Loaders. And, just like all planetary drives in our line up they are highly engineered and built to last.

HIGH QUALITY HYDRAULIC MOTORS

Auger Torque's huge buying power means we work closely with high quality suppliers to develop the most reliable attachments available on the market today.

NON-DISLODGEMENT SHAFT

Unique to Auger Torque, the Non-Dislodgement Shaft is a single piece drive shaft assembled top down and locked into the Earth Drill housing. This design guarantees that the shaft will never fall out, making for a safer work environment, not only for the operator but also any surrounding workers, a MUST-HAVE FEATURE for any safety conscious company.

AUGERTOROUF

EPICYCLIC GEARBOX

Torque is amplified by using the unique Auger Torque planetary gearbox. This system allows the motors output torque to be multiplied with extreme efficiency as well as ensuring the durability and reliability you need.

Visit the Solaris Attachments website to watch a demo

www.solarisattachments.com (888) 754-3609 | sales@solarisattachments.com

Features

- Unique Auger Torque planetary gearbox offering high efficiency and extreme durability
- Single piece drive shaft
- Large main shaft bearings
- Heavy duty steel construction
- Compatible with Auger Torques range of
- Alignment and Torque Monitoring products for accurate earth drilling applications
- Covered by Auger Torque's industry leading warranty

Applications

- Fencing
- Landscaping
- Tree Planting
- Pole and mast installations
- Road Signage

Specifications

Model		ML1100-13	ML1600-15	ML2100-17	MOUNTING FRAME
Torque Range	ft-lb	377-1103	471-1615	612-2100	P
Oil Pressure Range	psi	1015-2973	1015-3481	1015-3481	3
Oil Flow Range	gpm	5-13	7-15	7-17	
Speed Range	rpm	44-98	43-99	36-87	
Unit Height	inch	16	18	18	
Unit Width	inch	8	8	8	2-Way Swing
Unit Weight	lb	80	86	86	0
Output Shaft Std (adaptors available)	inch	2.56 Hex	2.56 Hex	2.56 Hex	2
Drilling Performance					
Auger Series		S4	S4	S4	
Auger Diameter	inch	4-16	4-16	4-20	4-Way Swing
Drilling Depth* *Dependent on ground type	ft	7-3	7-3	8-4	, , ,



Part of the Auger Torque Earthmoving range EARTH DRILLS | AUGERS & WEAR PARTS | MAST-BASED DRILLING RIG | TRENCHERS | HAMMERS

www.solarisattachments.com

(888) 754-3609 | sales@solarisattachments.com